



DATASHEET

# FortiGate®-1000C

## Accelerated, Proven Security for the Enterprise

By intercepting and inspecting network traffic at wire speeds, the FortiGate-1000C helps you identify and remove threats hidden within legitimate application traffic. With firewall performance of 20 Gbps and IPS throughput of 6 Gbps, the FortiGate-1000C is ideal for mid-to-large enterprise deployments. The FortiGate-1000C delivers the performance you need to control your organization's applications, data, and users without becoming a network bottleneck.

### The Power of Unified Threat Management (UTM)

The FortiGate-1000C security platform delivers industry-leading performance and flexibility. You can deploy the right blend of essential hardware-accelerated security technologies now and in the future to meet your evolving network requirements. These technologies include firewall, VPN, intrusion prevention, application control, and web content filtering, all managed from a 'single pane of glass' management console. The FortiGate-1000C also includes additional security technologies such as antivirus/antimalware, antispam, vulnerability management, and WAN optimization, allowing you to consolidate stand-alone devices.

The FortiGate-1000C gives you the ability to identify and stop numerous types of threats from a single device. For example, advanced application control enables you to define and enforce policies for thousands of applications running across your network, regardless of port or protocol used. Data leakage prevention technology, using a sophisticated pattern-matching engine, helps identify and prevent the accidental or intentional transfer of sensitive information outside of network perimeters, even when applications encrypt their communications.

The high port density and types of ports of the FortiGate-1000C gives you the freedom to create multiple security zones for various departments, users, access methods, and even devices. There are eight (8) shared RJ-45/SFP Gigabit Ethernet ports for deployment flexibility, as well as two (2) bypass-protected port to preserve network availability in the event of a device failure. In addition, 128 GB of onboard flash memory lets you deploy WAN optimization to reduce bandwidth consumption across your WAN connection, enable local reporting, or archive content locally.



### FortiOS The World's Most Advanced Security Operating System

FortiOS provides high performance, ultra low latency multi-threat security by leveraging the hardware acceleration provided by purpose-built FortiASIC processors. This combination of custom hardware and software gives you the best security and performance possible from a single device. FortiOS allows greater traffic visibility and more consistent, granular control over users, applications and sensitive data.

### The FortiASIC Advantage

FortiASIC processors power FortiGate platforms. With exclusive hardware, the purpose built, high performance Network, Security, and Content processors use intelligent and proprietary digital engines to accelerate resource intensive security services.

Challenge	Solution
Visibility and control of new applications and content	FortiGate devices deliver complete, comprehensive application control, enabling you to block unwanted traffic and behavior.
Time-sensitive applications require extremely low latency during transit	FortiGate-1000C appliance ensures that security is never a bottleneck. Up to 20 Gbps firewall performance and up to 8 Gbps IPSec VPN performance ensures optimal performance of latency-sensitive applications.
Internal network segmentation is difficult to deploy	FortiGate-1000C appliance with 24 hardware-accelerated switched ports permit a wide-array of deployments.
Applications are expected to perform well over the WAN	The FortiGate-1000C features 128 GB of onboard storage for WAN Optimization.
Eliminating blind spots caused by using multiple non-integrated security technologies	Fortinet combines core security technologies such as firewall, VPN, intrusion prevention, and application control into a single platform, providing an effective all-in-one solution.

## FortiGate Consolidated Security Solutions

Fortinet's consolidated security solutions provide an integrated set of core security and network services in a single, easy-to-manage, high-performance appliance that is capable of supporting a wide range of deployment scenarios. In addition, FortiGuard® Subscription Services include dynamic updates to ensure your security environment remains current and your corporate resources are protected against the latest threats.

Technical Specifications		FortiGate-1000C
<b>HARDWARE</b>		
Accelerated 10-GbE SFP+ Interfaces		2
Accelerated 10/100/1000 Interfaces (RJ-45)		12
Accelerated GbE SFP or 10/100/1000 Shared Interfaces		8
Accelerated 10/100/1000 Bypass Interfaces		2 pairs
10/100/1000 Management Interface		2
Maximum Network Interfaces		26
Internal Storage		128 GB
USB Ports (Client/Server)		1 / 1
<b>SYSTEM PERFORMANCE</b>		
Firewall Throughput (1518 / 512 / 64 byte UDP packets)		20 / 20 / 20 Gbps
Firewall Latency (64 byte UDP packets)		6 µs
Firewall Throughput (Packets Per Second)		30 Mpps
Concurrent Sessions (TCP)		7 Million
New Sessions/Sec (TCP)		190,000
Firewall Policies		100,000
IPSec VPN Throughput (512 byte packets)		8 Gbps
Gateway-to-Gateway IPSec VPN Tunnels		10,000
Client-to-Gateway IPSec VPN Tunnels		50,000
SSL-VPN Throughput		1.3 Gbps
Concurrent SSL-VPN Users (Recommended Max)		10,000
IPS Throughput		6 Gbps
Antivirus Throughput (Proxy Based / Flow Based)		1.7 / 3.1 Gbps
Virtual Domains (Default / Max)		10 / 250
Max Number of FortiAPs		512
Max Number of FortiTokens		5,000
Max Number of Registered FortiClients		8,000
High Availability Configurations		Active/Active, Active/Passive, Clustering
Unlimited User Licenses		Yes

Technical Specifications		FortiGate-1000C
<b>DIMENSIONS AND POWER</b>		
Height		3.5 in ( 88 mm)
Width		17 in ( 432 mm)
Length		16.4 in ( 416 mm)
Weight		24.6 lb ( 11.2 kg)
Rack Mountable		Yes
AC Power		100-240 VAC, 60-50 Hz
Max Current		110 V / 7 A, 220 V / 3.5 A
Power Consumption (AVG)		191.5 W
Power Consumption (Max)		230 W
Heat Dissipation		785 BTU/h
DC Power (FG-1000C-DC Required)		-48V VDC (Normal)
Redundant Power Supply (Hot-swappable)		Yes
<b>ENVIRONMENT AND CERTIFICATIONS</b>		
Operating temperature		32 - 104 °F (0 - 40 °C)
Storage temperature		-13 - 158 °F (-25 - 70 °C)
Humidity		20 to 90% non-condensing
Compliance		FCC Part 15 Class A, C-Tick, VCCI, CE, UL/cUL, CB
Certifications		ICSA Labs: Firewall, IPSec, IPS, Antivirus, SSL VPN

All performance values are "up to" and vary depending on system configuration. Antivirus performance is measured using 44 Kbyte HTTP files. IPS performance is measured using 1 Mbyte HTTP files.

Ordering Info	
Unit	SKU
FortiGate-1000C	FG-1000C
FortiGate-1000C-DC	FG-1000C-DC
Optional Accessories	SKU
FG-600C and FG-1000C AC Power Supply	SP-FG600C-PS

FortiGuard® Security Subscription Services deliver dynamic, automated updates for Fortinet products. The Fortinet Global Security Research Team creates these updates to ensure up-to-date protection against sophisticated threats. Subscriptions include antivirus, intrusion prevention, web filtering, antispam, vulnerability and compliance management, application control, and database security services.

FortiCare™ Support Services provide global support for all Fortinet products and services. FortiCare support enables your Fortinet products to perform optimally. Support plans start with 8x5 Enhanced Support with "return and replace" hardware replacement or 24x7 Comprehensive Support with advanced replacement. Options include Premium Support, Premium RMA, and Professional Services. All hardware products include a 1-year limited hardware warranty and 90-day limited software warranty.



### GLOBAL HEADQUARTERS

Fortinet Incorporated  
1090 Kifer Road, Sunnyvale, CA 94086 USA  
Tel +1.408.235.7700  
Fax +1.408.235.7737  
www.fortinet.com/sales

### EMEA SALES OFFICE – FRANCE

Fortinet Incorporated  
120 rue Albert Caquot  
06560, Sophia Antipolis, France  
Tel +33.4.8987.0510  
Fax +33.4.8987.0501

### APAC SALES OFFICE – SINGAPORE

Fortinet Incorporated  
300 Beach Road #20-01, The Concourse  
Singapore 199555  
Tel: +65-6513-3734  
Fax: +65-6295-0015



Copyright© 2013 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, and FortiGuard® are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance metrics contained herein were attained in internal lab tests under ideal conditions, and performance may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to the performance metrics herein. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any guarantees. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.

FG-1000C-DAT-R8-201305